



BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 7/2/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Indoor Candle
Trade name : Black Vanilla & Oud
UFI :
Product code : Candle - Black Vanilla & Oud
Type of product : Indoor Candle
Product group : Consumer product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

Use of the substance/mixture : Candle
Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Honey & Me Ltd
36 Panama Road Burton
on Trent Staffordshire,
DE13 0SQ

1.4. Emergency telephone number

01283 430300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, H412
Category 3
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains	: Hexyl cinnamic aldehyde; Benzyl salicylate; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone; Orange oil ; COUMARIN; Patchouli oil; Cyclamal; Helional; Timberol; Eugenol
Hazard statements (CLP)	: H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P321 - Specific treatment (see supplemental first aid instruction on this label).
Extra phrases	: For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bis(2-ethylhexyl) adipate substance with national workplace exposure limit(s) (PL)	CAS-No.: 103-23-1 EC-No.: 203-090-1 REACH-no: 01-2119439699-19	29.1 – 58.245	Not classified
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040-60	2 – 3.95	Eye Irrit. 2, H319
Ethylene brassylate	CAS-No.: 105-95-3 EC-No.: 203-347-8 REACH-no: 01-2119976314-33	1.7 – 3.47	Aquatic Chronic 2, H411
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092-50	0.9 – 1.78	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9 EC Index-No.: 607-754-00-5 REACH-no: 01-2119969442-31	0.8 – 1.58	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989-04	0.8 – 1.57	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	0.6 – 1.28	Eye Irrit. 2, H319
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	0.5 – 1	Acute Tox. 4 (Oral), H302
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353-35	0.3 – 0.67	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	0.2 – 0.4347	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.2 – 0.38	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Sandela	CAS-No.: 66068-84-6 EC-No.: 266-100-3	0.2 – 0.33	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272-42	0.1 – 0.26	Aquatic Chronic 3, H412
Patchouli oil	CAS-No.: 8014-09-3 EC-No.: 616-944-7 EC Index-No.: 616-944-7	0.1 – 0.2	Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Cyclamal	CAS-No.: 103-95-7 EC-No.: 203-161-7 REACH-no: 01-2119970582-32	0.1 – 0.14	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Helional	CAS-No.: 1205-17-0 EC-No.: 214-881-6 REACH-no: 01-2120740119-58	0.1 – 0.14	Skin Sens. 1B, H317 Repr. 2, H361 Aquatic Chronic 2, H411
Timberol	CAS-No.: 70788-30-6 EC-No.: 274-892-7	0.1 – 0.1	Skin Sens. 1B, H317
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802-33	0.1 – 0.1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
.beta.-Pinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 127-91-3 EC-No.: 204-872-5	≤ 0.00225	Flam. Liq. 3, H226

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	≤ 0.00186	Not classified
.alpha.-Pinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 80-56-8 EC-No.: 201-291-9	≤ 0.00015	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
---------------------------	---

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage temperature	: 25 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Store in a closed container.
Packaging materials	: Do not store in corrodable metal.

Germany

Storage class (LGK, TRGS 510)	: LGK 12 - Non-combustible liquids
-------------------------------	------------------------------------

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Joint storage table	:	LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
		LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
		LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
		LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
		LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13
Joint storage not permitted for	:	LGK 1, LGK 6.2, LGK 7				
Joint storage with restrictions permitted for	:	LGK 4.1A, LGK 4.3, LGK 5.1C				
Joint storage permitted for	:	LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13				

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Bis(2-ethylhexyl) adipate (103-23-1)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	400 mg/m³
Benzyl acetate (140-11-4)	
Belgium - Occupational Exposure Limits	
OEL TWA	62 mg/m³
	10 ppm
Denmark - Occupational Exposure Limits	
OEL TWA	61 mg/m³
	10 ppm
OEL STEL	122 mg/m³
	20 ppm
Ireland - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL STEL	30 ppm (calculated)
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzyl acetate (140-11-4)	
Romania - Occupational Exposure Limits	
OEL TWA	50 mg/m³
	8 ppm
OEL STEL	80 mg/m³
	13 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	62 mg/m³
	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m³
	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)
	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m³

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	309 mg/m³
	50 ppm
OEL STEL	618 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m³ (restrictive limit)
	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m³ (isomer mixture)
	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m³
	100 ppm
OEL STEL	900 mg/m³
	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m³ (1-(3-Methoxypropoxy)propan-1-ol)
	50 ppm (1-(3-Methoxypropoxy)propan-1-ol)
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSch (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Skin notation

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL STEL	308 mg/m³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m³
	50 ppm
KGV (OEL STEL)	450 mg/m³
	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m³
	50 ppm
WEL STEL (OEL STEL)	924 mg/m³ (calculated)
	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	300 mg/m³
	50 ppm
Kortidsverdi (OEL STEL)	375 mg/m³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Dipropylene glycol methyl ether)

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.alpha.-Pinene (80-56-8)	
Belgium - Occupational Exposure Limits	
OEL TWA	20 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	150 mg/m³
	25 ppm
TPRV (OEL STEL)	300 mg/m³
	50 ppm
Portugal - Occupational Exposure Limits	
OEL TWA	20 ppm (Turpentine and selected Monoterpenes)
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	113 mg/m³
	20 ppm
OEL chemical category	Sensitizer
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	150 mg/m³
	25 ppm
KGV (OEL STEL)	300 mg/m³
	50 ppm
OEL chemical category	Sensitizer
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	140 mg/m³
	25 ppm
Kortidsverdi (OEL STEL)	175 mg/m³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm (Turpentine and selected Monoterpenes)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.beta.-Pinene (127-91-3)	
Belgium - Occupational Exposure Limits	
OEL TWA	20 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	150 mg/m³
	25 ppm
TPRV (OEL STEL)	300 mg/m³
	50 ppm
Portugal - Occupational Exposure Limits	
OEL TWA	20 ppm (Turpentine and selected Monoterpenes)
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	113 mg/m³
	20 ppm
OEL chemical category	Sensitizer
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	150 mg/m³
	25 ppm
KGV (OEL STEL)	300 mg/m³
	50 ppm
OEL chemical category	Sensitizer
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	140 mg/m³
	25 ppm
Kortidsverdi (OEL STEL)	175 mg/m³ (value calculated)
	37.5 ppm (value calculated)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm (Turpentine and selected Monoterpenes)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:
Avoid all unnecessary exposure.
Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:
Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

Other information:
Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow. amber. Conforms to standard.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93.3 °C

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0.004395473 mm Hg (calculated value)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 22.736835 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Bis(2-ethylhexyl) adipate (103-23-1)	
LD50 oral rat	5600 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	8410 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 5.7 mg/l/4h
Vanillin (121-33-5)	
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vanillin (121-33-5)	
LD50 dermal	2600 mg/kg bodyweight
Ethylene brassylate (105-95-3)	
LD50 oral rat	> 5000 mg/kg (Source: ECHA)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)
Hexyl cinnamic aldehyde (101-86-0)	
LD50 oral rat	3100 mg/kg (Source: NLM_CIP)
LD50 oral	3100 mg/kg bodyweight
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPVS)
LC50 Inhalation - Rat	> 5 mg/l/4h
Benzyl salicylate (118-58-1)	
LD50 oral rat	2227 mg/kg (Source: NLM_CIP)
LD50 oral	2200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
Ethyl vanillin (121-32-4)	
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
Ethyl maltol (4940-11-8)	
LD50 oral rat	1150 mg/kg (Source: NLM_CIP)
LD50 oral	1200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)
Orange oil (8008-57-9)	
LD50 oral rat	4400 mg/kg (Source: NZ_CCID)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg (Source: NLM_CIP)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
COUMARIN (91-64-5)	
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
LD50 dermal rat	293 mg/kg (Source: ECHA_API)
Sandela (66068-84-6)	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	> 5.27 mg/l/4h
Benzyl acetate (140-11-4)	
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
LD50 oral	2490 mg/kg bodyweight

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzyl acetate (140-11-4)	
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)
Patchouli oil (8014-09-3)	
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)
Cyclamal (103-95-7)	
LD50 oral rat	3810 mg/kg (Source: NLM_CIP)
LD50 oral	3810 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)
Helional (1205-17-0)	
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)
Timberol (70788-30-6)	
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)
Eugenol (97-53-0)	
LD50 oral rat	1930 mg/kg (Source: NZ_CCID)
LD50 oral	2500 mg/kg bodyweight
Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
.alpha.-Pinene (80-56-8)	
LD50 oral rat	3700 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 5000 mg/kg (Source: CHEMVIEW)
.beta.-Pinene (127-91-3)	
LD50 oral rat	> 5000 mg/kg (Source: EPA_HPVS)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Bis(2-ethylhexyl) adipate (103-23-1)	
IARC group	3 - Not classifiable
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable
Eugenol (97-53-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aspiration hazard : Not classified

Orange oil (8008-57-9)	
Hydrocarbon	Yes
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s
.alpha.-Pinene (80-56-8)	
Hydrocarbon	Yes
.beta.-Pinene (127-91-3)	
Hydrocarbon	Yes

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Bis(2-ethylhexyl) adipate (103-23-1)	
LC50 - Fish [1]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	> 1.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])
Benzyl salicylate (118-58-1)	
LC50 - Fish [1]	1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
Ethyl maltol (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l
Eugenol (97-53-0)	
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
.alpha.-Pinene (80-56-8)	
LC50 - Fish [1]	0.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
EC50 - Crustacea [1]	41 mg/l (Exposure time: 48 h - Species: Daphnia magna)
12.2. Persistence and degradability	
BLACK VANILLA & OUD #EU56230F	
Persistence and degradability	Not established.
Bis(2-ethylhexyl) adipate (103-23-1)	
Persistence and degradability	Rapidly degradable
Vanillin (121-33-5)	
Persistence and degradability	Rapidly degradable
Ethylene brassylate (105-95-3)	
Persistence and degradability	Rapidly degradable
Hexyl cinnamic aldehyde (101-86-0)	
Persistence and degradability	Rapidly degradable
Benzyl salicylate (118-58-1)	
Persistence and degradability	Rapidly degradable
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (54464-57-2)	
Persistence and degradability	Rapidly degradable
Ethyl vanillin (121-32-4)	
Persistence and degradability	Rapidly degradable
Ethyl maltol (4940-11-8)	
Persistence and degradability	Rapidly degradable
Orange oil (8008-57-9)	
Persistence and degradability	Rapidly degradable
benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
COUMARIN (91-64-5)	
Persistence and degradability	Rapidly degradable

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Sandela (66068-84-6)	
Persistence and degradability	Rapidly degradable
Benzyl acetate (140-11-4)	
Persistence and degradability	Rapidly degradable
Patchouli oil (8014-09-3)	
Persistence and degradability	Rapidly degradable
Cyclamal (103-95-7)	
Persistence and degradability	Rapidly degradable
Helional (1205-17-0)	
Persistence and degradability	Rapidly degradable
Timberol (70788-30-6)	
Persistence and degradability	Rapidly degradable
Eugenol (97-53-0)	
Persistence and degradability	Rapidly degradable
Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable
.alpha.-Pinene (80-56-8)	
Persistence and degradability	Rapidly degradable
.beta.-Pinene (127-91-3)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
BLACK VANILLA & OUD #EU56230F	
Bioaccumulative potential	Not established.
Bis(2-ethylhexyl) adipate (103-23-1)	
BCF - Fish [1]	(27 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	8.94 (at 25 °C)
Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)
Ethylene brassylate (105-95-3)	
Partition coefficient n-octanol/water (Log Pow)	4.3 (at 25 °C (at pH 6.4-7)
Benzyl salicylate (118-58-1)	
Partition coefficient n-octanol/water (Log Pow)	4
Ethyl vanillin (121-32-4)	
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)
Ethyl maltol (4940-11-8)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 25 °C)

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Benzyl acetate (140-11-4)	
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)
Cyclamal (103-95-7)	
Partition coefficient n-octanol/water (Log Pow)	3.4 (at 35 °C)
Helional (1205-17-0)	
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C)
Timberol (70788-30-6)	
Partition coefficient n-octanol/water (Log Pow)	5.79 (at 25 °C (at pH 5.85)
Eugenol (97-53-0)	
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5)
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)
.alpha.-Pinene (80-56-8)	
Partition coefficient n-octanol/water (Log Pow)	4.1

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecological information	: Avoid release to the environment.
HP Code	: HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Orange oil ; .alpha.-Pinene ; .beta.-Pinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	BLACK VANILLA & OUD #EU56230F ; Hexyl cinnamic aldehyde ; Benzyl salicylate ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone ; Orange oil ; benzyl benzoate ; Sandela ; Patchouli oil ; Cyclamal ; Helional ; Timberol ; Eugenol ; .alpha.-Pinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	BLACK VANILLA & OUD #EU56230F ; Ethylene brassylate ; Hexyl cinnamic aldehyde ; Benzyl salicylate ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone ; Orange oil ; benzyl benzoate ; Sandela ; Benzyl acetate ; Patchouli oil ; Cyclamal ; Helional ; .alpha.-Pinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Orange oil ; .alpha.-Pinene ; .beta.-Pinene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content : 22.736835 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : Orange oil ,Sandela,Timberol are listed
SZW-lijst van mutagene stoffen : Orange oil ,Sandela,Timberol are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

BLACK VANILLA & OUD

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.